


Śruby dwustronne, długość części wkręcanej 1d



• Normy:

- DIN 938
- PN 82125
- ISO -

• Materiał i klasa:

- 5,8 / 8,8 / A2 / A4

• Pokrycie:

- cynk galwaniczny
- cynk termodyfuzyjny

d	M5	M6	M8	M10	M12	(M14)	M16	(M18)	M20
	-	-	M8x1	M10x1, 25	M12x1, 25	(M14x1, 5)	M16x1, 5	(M18x1, ,5)	M20x1, 5
	-	-	-	-	M12x1, 5	-	-	-	-
x_1	2,0	2,5	3,2	3,8	4,3	5,0	5,0	6,3	6,3
x_2	1,0	1,25	1,6	1,9	2,2	2,5	2,5	3,2	3,2
b_1	5	6	8	10	12	14	16	18	20
$b \mid \leq 125$	16	18	22	26	30	34	38	42	46
$b \mid 125 < \mid \leq 200$	22	24	28	32	36	40	44	48	52
$b \mid > 200$	-	-	-	45	49	53	57	61	65

d	(M22)	M24	(M27)	M30	(M33)	M36	(M39)	M42	(M45)	M48	(M52)
	(M22x 1,5)	M24x 2	(M27x 2)	M30x 2	(M33x 2)	M36x 3	(M39x 3)	M42x3	(M45x 3)	M48x3	(M52x 3)
x_1	6,3	7,5	7,5	9,0	9,0	10,0	10,0	11,0	11,0	12,5	12,5
x_2	3,2	3,8	3,8	4,5	4,5	5,0	5,0	5,5	5,5	6,3	6,3

b_1	22	24	25	30	32	35	38	42	45	48	52
$b \mid \leq 125$	50	54	60	66	72	78	84	90	96	102	110
$b \mid 125 < \mid \leq 200$	56	60	66	72	78	84	90	96	102	108	116
$b \mid > 200$	69	73	79	85	91	97	103	109	115	121	129

()- wymiary nie zalecane